\mathbf{i}	PLUME	BING FIXTURE SCHEDULE						
	EQ. ID	SERVICE CONNECTIONS (INCH)				BASIS OF DESIGN: PRIMAF	RY FIXTURE	
			CW	HW	W	V	MANUFACTURER	MODEL
\langle	P-1(R)	EXISTING WALL HUNG FLUSH TANK WATER CLOSET	1/2"		4"	2"	EXISTING	
\geq	P-2(N)	LAVATORY, COUNTER, ADA COMPLIANT	1/2"	1/2"	2"	1-1/2"	CORIAN/KOHLER	816P SINK/PURIS FAUCET
>	P-3(N)	KITCHEN SINK, ADA COMPLIANT	1/2"	1/2"	2"	2"	SEE ARCHITECTURAL	
<	P-4(N)	SHOWER, ADA COMPLIANT	1/2"	1/2"			KOHLER	PURIST SERIES I MULTI-FUNCTION KIT, PRESSURE I VALVE, PURIST S KIT, AND CLEARI SHOWER DRAIN
\geq	P-5(N)	RECLINING BATHING SYSTEM					ARJO	PARKER SERIES
\geq	P-6(E)	HANDWASH SINK, ADA COMPLIANT	1/2"	1/2"	2"	1-1/2"	EXISTING	
\geq	CW-1(N)	CLOTHES WASHER OUTLET BOX					IPS CORP.	CENTER DRAIN S
/	OB-1(N)	BATHING UNIT SUPPLY WALL BOX	1/2"	1/2"			IPS CORP.	MULTIBOX ANGL OR EQUAL
\geq	OB-2(N)	BATHING UNIT DRAIN WALL BOX			2"	2"	IPS CORP.	MULTIBOX OUTL
$\left(\right)$	FD-1(N)	FLOOR DRAIN, SHOWER		_	2"	1-1/2"	KOHLER	CLEARFLO SQUA

AIR TERMINAL SCHEDULE

\geq	EQ. ID	DESCRIPTION	TERMINAL TYP	E	AIR SIDE PERF	ORMANCE		BASIS OF DESIGN		COMMENT(S)	
$\langle \rangle$			FACE SIZE (INCH)	NECK SIZE	AIRFLOW (CFM)	ESP (IN. W.C.)	NOISE	MANUFACTURER	MODEL		🏠
\leq	EA-1(N)	DRYER EXHAUST VENT		4"				SEIHO	SFB SERIES	CUSTOM COLOR. COORDINATE WITH OWNER FOR COLOR SELECTION.	/2
(EA-2(N)	KITCHEN HOOD EXHAUST VENT		8"				SEIHO	SFX SERIES	CUSTOM COLOR. COORDINATE WITH OWNER FOR COLOR SELECTION.	
5	SA-1(N)	SQAURE FACE DIFFUSER W/ROUND NECK CONNECTION	24"X24"	8"	60 CFM	0.01 in-wg	<19	PRICE INDUSTRIES	SPD SERIES		
λ											

MISCELLANEOUS MECHANICAL EQUIPMENT SCHEDULE

EQ. ID	DESCRIPTION	ELECTRICAL	BASIS OF DESIGN		ACCESSORIES	COMMENT(S)
			MANUFACTURER	MODEL		
AD-1(N)	1-HR RATED ACCESS DOOR		(SEE ARCHITECTURAL)			
SD-1(N)	COMBINATION FIRE AND SMOKE DAMPER	(SEE NOTE)	RUSKIN	FSD35 8"X6"		COORDINATE WITH ELECTRICAL FOR ACTUATION AND POWER INTERFACE WITH BUILDING FIRE ALARM SYSTEM
SD-2(N)	COMBINATION FIRE AND SMOKE DAMPER	(SEE NOTE)	RUSKIN	FSD35G 24"X24"		COORDINATE WITH ELECTRICAL FOR ACTUATION AND POWER INTERFACE WITH BUILDING FIRE ALARM SYSTEM
-SD-3(N)	COMBINATION FIRE AND SMOKE DAMPER	(SEE NOTE)	RUSKIN	FSD35G 20"X16"		COORDINATE WITH ELECTRICAL FOR ACTUATION AND POWER INTERFACE WITH BUILDING FIRE ALARM SYSTEM
HD-1(N)	RANGE HOOD WITH INTEGRAL FAN AND FIRE SUPPRESSION SYSTEM. INTEGRAL FAN. REAR DISCHARGE	1.2 AMP, 115V/1PH	GREENHECK	GRRS-W-30-R-E-X	SELF-CONTAINED FIRE SUPPRESSION SYSTEM WITH ELECTRONIC DETECTION AND MANUAL PULL STATION AND REMOTE HORN STROBE. REMOTE USER INTERFACE (ADA COMPLIANT).	ARRANGE 4" STAND-OFF FROM WALL FOR REAR DISCHARGE DUCT TRANSITON AS APPROPRIATE. COORDINATE WITH OWNER FOR MOIUNTING OF USER INTERFACE, PULL STATION, AND HORN STROBE. COORDINATE WITH ELECTRICAL FOR SUPERVISED SHUT-OFF/TIMER CONTROL AT NURSI STATION AS APPLICABLE

	COMMENT(S)	
	EXISTING WALL-HUNG FLUSH TANK WATER CLOSET. CONTRACTOR TO REMOVE CLOSET AND COORDINATE WITH THE OWNER FOR TEMPORARY DURING RENOVATION. REINSTALL WATER CLOSET WITH NEW SEAT, GASKETS, AND FLUSH KIT.	
RIST K-14407-3 SINK		
S K-22178-G ON SHOWER VALVE E BALANCED SHOWER I SHOWER VALVE TRIM RFLO SQUARE N.		
ES	PROVIDE FLEXIBLE CONNECTIONS BETWEEN BATH UNIT AND SUPPLY AND DRAIN WALL BOXES.	$\sum_{i=1}^{n}$
	EXISTING FIXTURE TO REMAIN EXCEPT WHERE DELETED FROM THE PROJECT.	
N SERIES OUTLET BOX		\prec
GLE STOP BOX SERIES		\sim
TLET BOX OR EQUAL		
UARE SHOWER DRAIN.	COORDINATE WITH FIXTURE P-4(N)	

