

## **ADDENDUM #1**

### **NESBETT COURTHOUSE CAFÉ REMODEL PROJECT #ANC-C-22-0009**

Date: August 3, 2022

To All Plan Holders:

The following changes, additions, clarifications, and/or deletions are hereby made a part of the Contract Documents for the above noted project, fully and completely as if the same were fully contained therein. All other terms, conditions, and specifications of the original Invitation to Bid remain unchanged.

**This amendment must be acknowledged in the space provided on the Bid Schedule.**

The Submittal Date and Time is UNCHANGED. It remains: August 11, 2022 at 10:00 a.m.

The modifications directed by this Addendum #1 are described on this page and the following attachments:

- |                   |         |
|-------------------|---------|
| 1. Addendum Text: | 2 pages |
| 2. Attachment     | 4 pages |

#### **CHANGES TO ADDENDA**

1. None.

#### **SUBMITTED QUESTIONS AND ANSWERS:**

**“Will the floor access be covered with the new flooring, or will we need to install the new flooring maintaining access?”** Access needs to be maintained. Install new flooring in a manner that will allow floor access.

1. **“Who will be providing the casework?”** The Contractor will provide the casework.
2. **“The documents say that the owner has first right of refusal for equipment. Where will the equipment be stored?”** Yes, the owner wants to keep the equipment and will arrange storage.
3. **“Where is the loading dock?”** The loading dock is located at ground level, on the west side of the Nesbett Courthouse building.
4. **“Please clarify paint requirements for the door frame in regards to the two doors opening into the hallway.”** Door to remain as is. Trim to be painted to match adjacent wall color.
5. **“Please provide basis of design for the F01/F02 – New Storage Rack.”** Please see information attached to this addendum.
6. **“Detail 7/A401 identifies F22 New Wall Shelve but does not appear on A201. Please Clarify.”** It is located in location as shown on A401.
7. **“Sheet Note 18 and 19 on both A201 and A401 identify refrigerators as OFCI but the Equipment Schedule on A201 identifies it as OFCA/Re-Install. Please Clarify.”** The refrigerators will need to be re-installed only.

8. **“Sheet Note 4 on A401 identifies equipment as OFCI but Equipment Schedule on Sheet A201 identifies it as OFCA. Please clarify.”** This item will be purchased and installed prior to award of bid. Equipment will now need to be re-installed.

**END OF ADDENDUM #1**

Home > All Products > Shelving, Bins and Storage > Industrial Wire Shelving > Chrome Wire Shelving

## Chrome Wire Shelving Unit - 60 x 18 x 72"



[More Images & Video](#)

### 4 SHELF STARTER UNIT

Maximize storage in large office closets.

- Shelves adjust in 1" increments.
- Assemble in minutes. No tools required.
- Reduce dust and dirt accumulation.
- NSF certified.
- Optional 5" polyurethane swivel stem casters add 6" to height.
- [Add-On Units](#) and [Wire Shelving Accessories](#) available.

SPECIFY SIZE: 54" Height 63" Height 72" Height 86" Height 96" Height

MODEL NO.	DIMENSIONS W x D x H	SHELF CAP. (LBS.)	PRICE EACH		WT. (LBS.)	UNIT HEIGHT	IN STOCK SHIPS TODAY	
			1	3+				
H-2942-72	60 x 18 x 72"	650	\$242	\$230	84	72" Height	1	<a href="#">ADD</a>

SHIPS UNASSEMBLED VIA UPS

[Additional Info](#) [Accessories/Parts](#) [Shopping Lists](#) [Request a Catalog](#)

#### DIMENSIONS:

- Outside:
  - Width: Subtract 1/4" from dimensions in the chart.
  - Depth: Same as listed in the chart.
- Usable Loading Area (Due to Posts):
  - Width & Depth: Subtract 2 3/4" from outside dimensions.
- Posts (Single Piece Construction): 1" Diameter
- Shelf Thickness: 1 1/4"

#### MATERIAL:

- Chrome-plated carbon steel
- Rust resistant, not rust proof.

#### TEMPERATURE:

- -20° to 120° F

#### CAPACITY:

- Shelf capacity listed in the chart is:
  - The capacity for each shelf without casters.
  - Based on evenly distributed loads.
- Total Starter Unit with Additional Shelves: 4,800 lbs
- Total Add-on Unit: 3,000 lbs

#### USAGE:

- For hand-loading only. (Not for use with forklifts.)

#### CASTERS: (Sold Separately)

- Dimensions: 5 x 1 1/4"
- Add 5 3/4" to the height of the unit.
- Capacity: 1,000 lbs per kit (250 lbs per caster)
- NSF Certified (National Sanitary Foundation)

Availability: [In Stock](#)  
Unit Weight: 84 lbs.

[Instructions](#)

[Catalog Page 446](#)

[Email Item](#)



RELATED ITEMS

SAME DAY SHIPPING

HUGE SELECTION IN STOCK

SHIPS FROM 12 LOCATIONS

Chrome Wire Shelving Unit - 48 x 18 x 72"



More Images & Video

4 SHELF STARTER UNIT

Maximize storage in large office closets.

- Shelves adjust in 1" increments.
- Assemble in minutes. No tools required.
- Reduce dust and dirt accumulation.
- NSF certified.
- Optional 5" polyurethane swivel stem casters add 6" to height.
- [Add-On Units](#) and [Wire Shelving Accessories](#) available.

SPECIFY SIZE: 54" Height 63" Height 72" Height 86" Height 96" Height

MODEL NO.	DIMENSIONS W x D x H	SHELF CAP. (LBS.)	PRICE EACH		WT. (LBS.)	UNIT HEIGHT	IN STOCK SHIPS TODAY
			1	3+			
H-2941-72	48 x 18 x 72"	800	\$193 ea. any qty.		66	72" Height	1 <a href="#">ADD</a>

SHIPS UNASSEMBLED VIA UPS

[Additional Info](#) [Accessories/Parts](#) [Shopping Lists](#) [Request a Catalog](#)

- DIMENSIONS:
- Outside:
    - Width: Subtract 1/4" from dimensions in the chart.
    - Depth: Same as listed in the chart.
  - Usable Loading Area (Due to Posts):
    - Width & Depth: Subtract 2 3/4" from outside dimensions.
  - Posts (Single Piece Construction): 1" Diameter
  - Shelf Thickness: 1 1/4"
- MATERIAL:
- Chrome-plated carbon steel
  - Rust resistant, not rust proof.
- TEMPERATURE:
- -20° to 120° F
- CAPACITY:
- Shelf capacity listed in the chart is:
    - The capacity for each shelf without casters.
    - Based on evenly distributed loads.
  - Total Starter Unit with Additional Shelves: 4,800 lbs
  - Total Add-on Unit: 3,000 lbs
- USAGE:
- For hand-loading only. (Not for use with forklifts.)
- CASTERS: (Sold Separately)
- Dimensions: 5 x 1 1/4"
  - Add 5 3/4" to the height of the unit.
  - Capacity: 1,000 lbs per kit (250 lbs per caster)
  - NSF Certified (National Sanitary Foundation)

Availability: [In Stock](#)  
Unit Weight: 66 lbs.  
[Instructions](#)  
[Catalog Page 446](#)  
[Email Item](#)



RELATED ITEMS

SAME DAY SHIPPING

HUGE SELECTION IN STOCK

SHIPS FROM 12 LOCATIONS