



SHAFT WALLS

GA FILE NO. WP 7008		PROPRIETARY†	1 HOUR FIRE	35 to 39 STC SOUND
GYPSUM WALLBOARD, STEEL C-H STUDS One layer 1" x 24" proprietary type X gypsum panels inserted between 2 1/2" floor and ceiling J runners with H section of 2 1/2" proprietary vented C-H steel studs between panels. OPPOSITE SIDE: One layer 5/8" proprietary type X gypsum wallboard or gypsum veneer base applied parallel to studs with 1" Type S drywall screws 12" o.c. STC estimate based on 1" mineral fiber insulation in stud space. (NLB)				
PROPRIETARY GYPSUM BOARD CertainTeed Gypsum, Inc. Lafarge North America Inc. PABCO Gypsum United States Gypsum Company			5/8" ProRoC™ Type C Gypsum Panels 5/8" Firecheck® Type C 5/8" FLAME CURB® Super 'C'™ 5/8" SHEETROCK® Brand gypsum Panels, FIRECODE® C Core 1" SHEETROCK® Brand Gypsum Liner panels	
			Thickness: Limiting Height: Approx. Weight: Fire Test: Sound Test:	3 1/8" Refer to manufacturer 8 psf UL R1319, 88NK2747, 2-8-88, UL Design U469 Estimated
†Contact the manufacturer for more detailed information on proprietary products.				